



Product No: 565167, 594435, 565116, 565183, 578558, 567533

## Dex III/Merc ATF

Multi-Purpose for DEXRON®/MERCEN® Applications

### Description

Unimark™ Dex III/Merc ATF is a premium, multi-functional automatic transmission fluid designed to service most General Motors, Ford Motor Company, and many Chrysler Corporation vehicles. This product may be used wherever General Motors DEXRON®, DEXRON®-II, DEXRON®-IIE, DEXRON®-III, and where Ford MERCON® is recommended.

Unimark™ Dex III/Merc ATF has outstanding low temperature properties, controlled frictional characteristics, outstanding resistance to oxidation, and can be used in many industrial applications calling for premium hydraulic oils where long life and superior performance are required.

### Application

- Dex III/M — All General Motors vehicles requiring DEXRON®, DEXRON®-II, DEXRON®-IIE, DEXRON®-III G & H
- D-III/M — All Ford motor company vehicles requiring MERCON®
- D-III/M — All GM Allison heavy duty transmissions where DEXRON®-II or DEXRON®-III, C-3 or C-4 fluids are recommended
- Industrial applications such as air compressors or skid steer loaders where the above fluids are recommended.

### Benefits

- Multi-purpose ATF D-III/M recommended for most cars since 1983
- Outstanding oxidation life with D-III/M and Type F
- Mixes safely with all OEM fluids
- Proper frictional control for General Motors, Ford, and Chrysler transmissions



Martin Lubricants - A Division of Martin Operating Partnership L.P.  
Smackover, AR 71762 • USA Phone 800-864-6275 • [www.MartinLubricants.com](http://www.MartinLubricants.com)



Product No: 565167, 594435, 565116, 565183, 578558, 567533

## PERFORMANCE RATING

General Motors	DEXRON®, DEXRON®-II, DEXRON®-II E, DEXRON®-III, DEXRON®-III G, DEXRON®-III H
Ford Motor Company	M — MERCON®
Caterpillar	TO-2
Denison	HF-O
Allison	C-3, C-4

## TYPICAL PROPERTIES

	Method	Dex/Merc ATF
Specific Gravity @15.6C	D-1298	0.8644
Viscosity, cSt at 40°C	D-445	46.55
Viscosity, cSt at 100°C	D-445	8.57
Low Temperature Pumping, cP	D-2983	18,500 @-40°C
Viscosity Index	D-2270	164
Flash Point, °C	D-92	226
Flash Point, °F	D-92	439
Pour Point, °C	D-97	-51
Pour Point, °F	D-97	-60
Color	Visual	red

The information on this Product Data Sheet is believed to be accurate and is typical of current production. Specifications are subject to change without notice. For additional qualifications, please contact Martin Technical Service Department.

**Health and Safety Information:** See separate Safety Data Sheets available on request.

**Unimark™** and **Martin Lubricants™** are trademarks of Martin Lubricants. All other marks are property of their respective owners.

**DEXRON®** and **MERCON®** are registered trademarks of General Motors and Ford Motor Company, respectively.



Martin Lubricants - A Division of Martin Operating Partnership L.P.  
Smackover, AR 71762 • USA Phone 800-864-6275 • [www.MartinLubricants.com](http://www.MartinLubricants.com)