

SECTION 1 PRODUCT AND COMPANY IDENTIFICATION

Product: 4-Cycle Synthetic Blend Motorcycle Engine Oil SAE 10W-40

4-Cycle Synthetic Blend Motorcycle Engine Oil SAE 20W-50

CAS Registry Number: Not applicable for mixtures

Synonyms: Motorcycle Engine Oil, Premium Motorcycle Oil, Xtreme Motorcycle Oil

Generic/Chemical Name: Petroleum hydrocarbon fluid
Product Type: Motorcycle Engine Oil

Martin Lubricants; Emergency: ChemTrec 800-424-9300

A Division of Martin Operating Partnership L.P.

 484 East 6<sup>th</sup> Street
 Information:
 870-881-8700

 Smackover, AR 71762
 Fax:
 870-864-8656

USA www.martinlubricants.com

## SECTION 2 HAZARDS IDENTIFICATION

Signal Word: CAUTION

Hazard Statements: MAY CAUSE EYE IRRITATION

MAY CAUSE SKIN IRRITATION

HOT VAPORS MAY CAUSE RESPIRATORY IRRITATION

HARMFUL IF SWALLOWED

Precautionary Measure: Do not eat, drink or smoke when using this product. Avoid contact with eyes,

skin and clothing. Wash thoroughly after handling.

OSHA/HCS Status: This material is considered non-hazardous by OSHA Hazard Communication

Standard (29 CFR 1910.1200)

	NPCA-HMIS	KEY
HEALTH:	1	0 = Minimal
FIRE:	1	1 = Slight
REACTIVITY:	0	2 = Moderate
SPECIFIC HAZARD:	N/A	3 = Serious
PROTECTION INDEX:	В	4 = Severe

Eye Contact: This product is not normally expected to cause eye irritation. Avoid prolonged

contact with the eyes, which may cause mild eye discomfort, tearing, or

blurring of vision. Based on data from similar materials.

**Skin Contact:** This product is not expected to cause skin irritation. Prolonged or repeated

contact may lead to an allergic skin sensitization in some people and dermatitis (dryness, chapping and reddening of skin). Based on component

data and data from similar materials.

**Inhalation:** Overexposure by inhalation of hot material may cause nonspecific discomfort,

such as nausea, headache, or weakness. Caution should be taken to prevent forming aerosol or misting of this product without proper respiratory protection.



**Ingestion:** Do not ingest. Due to the expected concentration of oil (70-100%) ingestion is

expected to be relatively non-toxic unless lung aspiration occurs. Aspiration may lead to chemical pneumonitis, which is characterized by pulmonary edema and hemorrhage and may be fatal. Signs of lung involvement include increased respiratory rate, increased heart rate, and a bluish discoloration of the skin. Coughing, choking, and gagging are often noted at the time of aspiration. Gastrointestinal discomfort may develop, followed by vomiting with a further risk of aspiration. This product has laxative properties and may result

in abdominal cramps and diarrhea.

SECTION 3 COMPOS	COMPOSITION / INFORMATION ON INGREDIENTS		
INGREDIENTS	CAS#	% Vol	
Hydro-treated paraffinic distillates	64742-54-7 64742-65-0	75-85	
Proprietary additives	68649-42-3 74499-35-7 132752-19-3	15-25	
Zinc salts of dialkyl dithiophosphoric acid	68649-42-3	<0.5	

There are no additional ingredients present which the current knowledge and in concentration applicable, are classified as hazardous to health or environment and hence require reporting in this section.

SECTION 4	FIRST AID MEASURES
-----------	--------------------

Eye Contact: Immediately flush eyes with large amounts of water and continue flushing

until irritation subsides. If irritation persists call a physician. If material is hot,

treat for thermal burns and take victim to hospital immediately.

Skin Contact: Remove contaminated clothing. Wash contaminated area thoroughly with

soap and water. If redness or irritation occurs, seek medical attention. If material is hot, submerge injured area in cold water. If victim is severely burned, remove to a hospital immediately. Wash contaminated clothing

before reuse.

Inhalation: If overcome by inhalation of hot vapors, remove to fresh air. Use oxygen if

there is difficulty breathing or artificial respiration if breathing has stopped. Do not leave victim unattended. Seek immediate medical attention if

necessary.

**Ingestion:** DO NOT INDUCE VOMITING. Do not induce vomiting due to aspiration

hazard. Immediately give 2 glasses of water. Never give anything by mouth to an unconscious person. Should vomiting occur; lower head below knees

to avoid aspiration. Seek immediate medical attention.

### SECTION 5 FIRE FIGHTING MEASURES

Flash Point: by Cleveland Open Cup, ASTM D 92

 10W-40
 20W-50

 224°C
 234°C

 (435°F)
 (453°F)

Upper Flammable Limit: Not determined
Lower Flammable Limit: Not determined



Use dry chemical, foam, water fog or carbon dioxide **Extinguishing Media:** 

Special Fire Fighting

**Procedures:** 

Water may be ineffective but can be used to cool containers exposed to heat or flame. Caution should be exercised when using water or foam as frothing may occur, especially if sprayed into containers of hot, burning

liquid.

Unusual Fire and **Explosion Hazards:**  Dense smoke may be generated while burning. Toxic fumes, gases or vapors may evolve on burning. Heavy flammable vapors may settle along ground level and low spots to create an invisible fire hazard. The vapors

may extend to sources of ignition and flash back.

By-products of Combustion:

**SECTION 6** 

Oxides of C, Zn, Ca, Mg, P and S. Additional byproducts include hydrogen

sulfide, alkyl mercaptan and other sulfides

Not determined **Auto-ignition Temperature:** 

**Explosion Data:** Not determined. Care should always be exercised in dust/mist areas.

## ACCIDENTAL RELEASE MEASURES

Spill Procedures (Land):

Immediately turn off or isolate any source of ignition (pilot lights, electrical equipment, flames, and heaters). Evacuate area and ventilate. Personnel wearing proper protective equipment should contain spill immediately with inert materials (sand, earth, chemical spill pads of cotton) by forming dikes. Dikes should be placed to contain spill in a manner that will prevent material from entering sewers and waterways. Large spill, once contained, may be picked up using explosion proof, non-sparking vacuum pumps, shovels, or buckets, and disposed of in suitable containers for disposal. If a large spill occurs notify appropriate authorities.

Spill Procedures (Water):

Remove from surface by skimming or with suitable adsorbents. If a large

spill occurs notify appropriate authorities.

**Waste Disposal** 

Method:

All disposals must comply with federal, state, and local regulations. The material, if spilled or discarded may be a regulated waste. Refer to state and local regulations. Department of Transportation regulations may apply for transporting this material when spilled. See Section 14.

CAUTION - If spilled material is cleaned up using a regulated solvent, the resulting waste mixture may be regulated.

#### **SECTION 7 HANDLING AND STORAGE**

Keep containers closed when not in use. Do not transfer to unmarked **Handling Procedures:** 

containers. Fire extinguishers should be kept readily available. See NFPA 30 and OSHA 1910.106 -- Flammable and Combustible Liquids. Empty containers retain product residue which may exhibit hazards of material, therefore do not pressurize, cut, glaze, weld, or use for any other purposes.

Return drums to reclamation centers for proper cleaning and reuse.

Storage Procedures: Store containers away from heat, sparks, open flame, or oxidizing materials.

Additional Information: No additional information.

#### **SECTION 8 EXPOSURE CONTROLS / PERSONAL PROTECTION**

**INGREDIENTS ACGIH OSHA** NIOSH Hazard Risk Phrase TLV **PELS** STEL Class \*



Hydro-treated paraffinic distillates	5 mg/m <sup>3</sup> oil mist	5 mg/m <sup>3</sup> oil mist	10 mg/m <sup>3</sup> oil mist	N/A	N/A
Proprietary additives	5 mg/m <sup>3</sup> oil mist	5 mg/m <sup>3</sup> oil mist	10 mg/m <sup>3</sup> oil mist	N/A	N/A
Zinc salts of dialkyl dithiophosphoric acid	5 mg/m <sup>3</sup> oil mist	5 mg/m <sup>3</sup> oil mist	5 mg/m <sup>3</sup> oil mist	N/A	N/A

<sup>\*</sup> Hazard Class & Risk Phrase: These columns are only completed for ingredients which are classified as hazardous under EU Directive (67/548/EEC, as amended) and are present in sufficient concentration to make the overall substance hazardous. In all other situations, the column will be completed as "Not Applicable".

#### **ABBREVIATIONS:**

NE: None Established NA: Not Applicable (1): NIOSH Guidelines (2) "Manufacturer Recommendation" Short Term Exposure Limit ND: Not Determined

Personal Protection: Applicable mainly to persons in repeated contact situations such as

packaging of product, service/maintenance, and cleanup/spill control

personnel.

Respiratory Protection: None required if airborne concentrations are maintained below threshold

limits listed on page 1. Otherwise a respiratory protection program meeting OSHA 1910.134 and ANSI Z88.2 requirements must be followed. Where misting may occur, wear an MSHA/NIOSH approved (or equivalent) half-

mask form dust/mist air- purifying respirator.

Eye Protection: Eye protection is always recommended. If material is handled such that it

could be splashed into the eyes, wear safety glasses with side shields or

vented/splash proof goggles (ANSI Z87.1 or approved equivalent).

Hand Protection: Impervious gloves such as neoprene or Nitrile® rubber to avoid skin

sensitization and absorption.

Other Protection: Use of an apron and over-boots of chemically impervious materials such as

neoprene or Nitrile® rubber is recommended to avoid skin sensitization. If handling hot material use insulated protective equipment. Launder soiled clothes. Properly dispose of contaminated leather articles and other

materials, which cannot be decontaminated.

Local Control Measures: Use adequate ventilation when working with material in an enclosed area.

Mechanical methods such as fume hoods or area fans may be used to reduce localized vapor/mist areas. If vapor or mist is generated when the material is heated or handled, adequate ventilation in accordance with good engineering practice must be provided to maintain concentrations below the specified exposure. Eyewash stations and showers should be available in

areas where this material is used and stored.

Other: Consumption of food and drink should be avoided in work areas where

product is present. Always wash hands and face with soap and water before

eating, drinking, or smoking.

## SECTION 9 PHYSICAL AND CHEMICAL PROPERTIES

Vapor Pressure: Negligible at STP (Standard Temperature and Pressure, 25°C at 1 ATM)



 Gravity by ASTM D 1298:
 10W-40
 20W-50

 API Gravity
 30.1
 27.7

 Specific Gravity @ 15.6°C
 0.8756
 0.8888

 Density @ 15.6°C
 7.291
 7.401

**Solubility** Negligible in water, soluble in hydrocarbon solvents

Percent Volatile: Negligible at STP

Vapor Density, Air = 1: >1 at STP

Evaporation Rate, Negligible at STP

n-Butyl Acetate = 1:

Odor: Mild petroleum hydrocarbon odor

Appearance: Amber, clear fluid

 Viscosity by ASTM D 445:
 10W-40
 20W-50

 cSt at 40°C (104°F)
 83.55
 152.35

 cSt at 100°C (212°F)
 12.48
 17.89

**Boiling Point:** Not determined. Expected to be > 260°C (500°F).

 Pour Point (°C):
 10W-40
 20W-50

 by ASTM D 97
 -35
 -20

Molecular Weight: Not determined.

## SECTION 10 STABILITY AND REACTIVITY

Stability: Material is stable at room temperature and pressure.

Conditions To Avoid: Avoid high temperatures and product contamination.

Incompatibility With Other

Materials:

Avoid contact with acids and oxidizing materials.

**Decomposition Products:** Smoke, carbon monoxide and dioxide, and other aldehydes of incomplete combustion. Oxides of C, Zn, P, Mg and S. Hydrogen sulfide and alkyl

mercaptans and other sulfides may be released.

Hazardous Polymerization: Will not occur.

### SECTION 11 TOXICOLOGICAL INFORMATION

Oral Toxicity: Not determined

Dermal Toxicity: Not determined

Inhalation Toxicity: On rare occasions, prolonged and repeated exposure to oil mist poses a

risk of pulmonary disease such as chronic lung inflammation. This condition is usually asymptotic as a result of repeated small aspirations. Shortness of breath and cough are the most common symptoms. Based on data from

similar materials.

**Dermal Sensitization:** Prolonged or repeated contact may make skin more sensitive to other skin

sensitizers. Based on data from similar materials.



Chronic Toxicity: Not determined
Carcinogenicity: Not determined

Mutagenicity: This product contains zinc alkyl dithiophosphates (ZDP). Several ZDPs

have been reported to have weak mutagenic activity in cultured mammalian cells but only at concentrations that were toxic to the test cells. We do not believe that there is any mutagenic risk to workers exposed to this product's

concentration level of ZDP.

Reproductive Toxicity: Not determined Teratogenicity: Not determined

Other: This product contains petroleum base oils, which may be refined by various

processes including severe solvent extraction, severe hydro-cracking, or severe hydro-treating. None of the oils require a cancer warning under the OSHA Hazard Communication Standard (29 CFR 1910.1200). These oils have not been listed in the National Toxicology Program (NTP) Annual Report nor have they been classified by the International Agency for Research on Cancer (IARC) as; carcinogenic to humans (Group 1), probably carcinogenic to humans (Group 2A), or possibly carcinogenic to

humans (Group 2B).

SECTION 12 ECOLOGICAL INFORMATION

Environmental Toxicity: This material may be toxic to aquatic organisms and should be kept out of

sewage and drainage systems and all bodies of water.

Environmental Fate: No data available

SECTION 13 DISPOSAL CONSIDERATIONS

Waste Disposal: Under RCRA it is the responsibility of the user of the product to determine at

the time of disposal whether the product meets RCRA criteria for hazardous waste. Waste management should be in full compliance with federal, state,

and local laws.

Disposal Consideration: Place used, contaminated, or excess material into disposable containers

and dispose of in a manner consistent with local and state regulations. Contact local environmental or health authorities for approved disposal of

this material. Most used oil is reclaimed or incinerated.

## SECTION 14 TRANSPORT INFORMATION

		Non-Bulk		
	<b>Bulk Shipping</b>	Shipping	<b>Identification No.</b>	<b>Hazard Class</b>
US DOT	Not required	Not required	Not required	Not required
Canadian TDG	Not required	Not required	Not required	Not required
European	Not required	Not required	Not required	Not required
IMDG	Not required	Not required	Not required	Not required
IATA - DGR	Not required	Not required	Not required	Not required

Other: See 49 CFR for additional requirements for descriptions, allowed modes of

transport, and packaging. For more information concerning spills during transport, consult latest DOT Emergency Response Guidebook for

Hazardous Materials Incidents, DOT P 5800.3.



SECTION 15 REGULATORY INFORMATION

Clean Water Act/Oil

Pollution Act:

Under Section 311 of the Clean Water Act (40 CFR 110) and the Oil
Pollution Act:

Under Section 311 of the Clean Water Act (40 CFR 110) and the Oil
Pollution Control Act of 1990, this material is considered an oil. Any spills or

discharges that produce a visible sheen or film on surface of water, or in waterways, ditches, or sewers leading to surface water must be reported.

Contact the National Response Center at 800-424-8802.

**TSCA:** All components of this material are listed in the U.S. TSCA Inventory.

Other TSCA: Not applicable

SARA Title III: Section 302/304 Extremely Hazardous Substances: None

Section 311/312 <u>Hazard Categorization:</u>

Acute (immediate health effects): Yes
Chronic (delayed health effects): No
Fire (hazard): No
Reactivity (hazard): No

Pressure (sudden release hazard): No

Section 313 Toxic Chemicals: Zinc <0.10%

CERCLA: For stationary sources - reportable quantity: Not determined

Due to:

For moving sources - reportable quantity:

Not applicable

Not determined

Not applicable

Recommend contacting the local authorities in the event of any type of spill to determine local reporting requirements and also to aid in the cleanup.

California Prop. 65: Not applicable

# SECTION 16 OTHER INFORMATION

#### Glossary:

ACGIH – American Conference of Governmental Industrial Hygienists; ANSI – American National Standards Institute; Canadian TDG – Canadian Transportation of Dangerous Goods; CAS – Chemical Abstract Service; Chemtrec – Chemical Transportation Emergency Center (US); CHIP – Chemical Hazard Information and Packaging; DSL – Domestic Substances List; EC – Equivalent Concentration; EH40 (UK) – HSE Guidance Note EH40 Occupational Exposure Limits; EPCRA – Emergency Planning and Community Right-To-Know Act; HMIS – Hazardous Material Information Service; LC – Lethal Concentration; LD – Lethal Dose; NFPA – National Fire Protection Association; OEL – Occupational Exposure Limits; OSHA – Occupational Safety and Health Administration, US Department of Labor; PEL – Permissible Exposure Limit; SARA (Title III) – Superfund Amendments and Reauthorization Act; SARA 313 – Superfund Amendments and Reauthorization Act, Section 313; SCBA – Self-Contained Breathing Apparatus; STEL – Short Term Exposure Limit; TLV – Threshold Limit Value; TSCA – Toxic Substances Control Act Public Law 94-469; TWA – Time Weighted Value; US DOT – US Department of Transportation; WHMIS – Workplace Hazardous Materials Information System.

This product may be formulated in part with components purchased from other companies. In many instances, especially when proprietary or trade secret materials are used, Martin Lubricants; A Division of Martin Operating Partnership L.P., must rely upon information provided by the material manufacturers or distributors.

Prepared by: David Collins

File: SDS – 4 Cycle Synthetic Blend Motorcycle Engine Oil

4 CYCLE SYNTHETIC BLEND MOTORCYCLE ENGINE OIL



Revision: 08/16/20013

Safety Data Sheet compiled in accordance with ANSI Z400.1-2004 Standard - United States and the EU Safety Data Sheet Directive 91/155/EEC and the EU Safety Data Sheet Directive 91/155/EEC.

Information provided in this Safety Data Sheet is considered accurate and reliable based on information issued from internal and outside sources to the best of Martin Operating Partnership's knowledge; however, Martin Operating Partnership makes no representations, guarantees or warranties, expressed or implied, of merchantability or fitness for the particular purpose, regarding the accuracy of such information or the result to be obtained from the use thereof or as to the sufficiency of information herein presented. Martin Operating Partnership assumes no responsibility for injury to recipient or to third persons or for any damage to any property and recipient assumes all such risks.