



# AIR TOOL OIL

Lubrication & Anti-Wear Protection  
For Pneumatic Air Tools



REV: 05.17.2017



## DESCRIPTION

Gard™ Air Tool Oil is formulated to provide lubrication and anti-wear protection for pneumatic air tools used in foundries, tool and die shops, machine shops, pattern shops, and steel fabrication shops. Blended from specially selected base oils with rust and oxidation inhibitors and antiwear additives.

## BENEFITS

- Thermally stable, gives excellent year-round performance
- Helps prevent wear and prolongs tool life
- Compatible with other petroleum-based air tool oils
- Excellent free-flowing lubrication in cold weather conditions

## APPLICATION

- Recommended for use in drip lubricating systems supplying air power tools.

TYPICAL PROPERTIES	METHOD	ATO
Specific Gravityt at 15.6°C	D-1298	0.9135
Viscosity, cSt at 40°C	D-445	30.4
Viscosity, cSt at 100°C	D-445	4.6
Flash Point, COC °C (°F)	D-92	168 (334)
Pour Point, °C (°F)	D-97	-39 (-38)
ML Reference No.		576384



### NOTE:

The information on this Product Data Sheet is believed to be accurate and is typical of current production. Specifications are subject to change without notice. For additional qualifications, please contact Martin Lubricants Technical Service Department.

**Health And Safety Information** See separate Safety Data Sheets available on request.

**Gard™ and Martin Lubricants™** are trademarks of Martin Lubricants. All other marks are property of their respective owners