

ANTIFREEZE COOLANT Automotive, Heavy-Duty Antifreeze Premixed and ready to use



REV:

07.11.2017



DESCRIPTION

Gard^M Antifreeze/Coolant is a concentrated low silicate fluid for use in radiators of automotive, heavy-duty, and industrial equipment. This unique product protects against surfaces including aluminum and rubber parts.

Gard™ Antifreeze/Coolant 50-50 is a pre-mixed low silicate fluid for use in radiators of automotive, heavy-duty, and industrial equipment. This unique product protects against corrosion on all surfaces including aluminum, cast iron, and rubber parts.

Gard^M Antifreeze/Coolants are formulated with ethylene glycol based antifreeze to prevent freezing and overheating and contains corrosion inhibitors to protect against rust and corrosion and blocking of internal radiator passages.

BENEFITS

- May be used in aluminum or cast iron engines
- Premixed and ready to use
- Helps stop rust and corrosion
- Compatible with all conventional antifreeze/coolants

APPLICATION

 Automotive, heavy-duty trucks, off road equipment, and other applications such as stationary engines as a yearround antifreeze and summer coolant

TYPICAL PROPERTIES	METHOD	Antifreeze Coolant Concentrate	Antifreeze Coolant Concentrate
Specific Gravity at 15.6℃	D-1122	1.10-1.145	1.10-1.145
pH Concentrate	D-1287	11.0 max.	11.0 max.
Reserve Alkalinity	D-1121	10 min.	10 min.
Freeze Point, 50% °C (°F)	D-1177	-37 (-34) max.	-37 (-34) max.
Foaming Tendency	D-1881	50 mL/3 Sec max.	50 mL/3 Sec max.
Ash, % Mass	D-1119	1.5	1.5
Color	Visual	Fluorescent Green	Fluorescent Green



NOTE:

The information on this Product Data Sheet is believed to be accurate and is typical of current production. Specifications are subject to change without notice. For additional qualifications, please contact Martin Lubricants Technical Service Department.

Health And Safety Information See separate Safety Data Sheets available on request.

Gard™ and Martin Lubricants™ are trademarks of Martin Lubricants. All other marks are property of their respective owners

