



RIG ROCK DRILL OIL

Ashless Formulation

For use in lubricating all types of pneumatic equipment



REV: 05.17.2017



DESCRIPTION

Gard™ Rig Rock Drill Oil is produced from premium base oils selected for their ability to minimize carbon deposits and fortified with tackiness additives to cling to moving parts of pneumatic percussion tools.

Gard Rig Rock Drill Oil is recommended for use in lubricating all types of pneumatic equipment such as jackhammers, pavement breakers, stoppers, drifters and down home drills in road construction, quarries, and mining.

BENEFITS

- ▣ Reduced heat in pneumatic tools
- ▣ Low fogging tendencies
- ▣ Environmentally friendly ashless formulation

APPLICATION

- Pneumatic percussion tools in quarries and road construction and other rock drilling or breaking applications
- Pneumatic tools in a wide variety of applications where tack additives are recommended

RECOMMENDED TEMPERATURES

ISO 100

Operating Range °F (°C): 40-80 (4-27)

TYPICAL PROPERTIES	METHOD	ISO 100
Specific Gravity @15.6°F	D-1298	0.925
Viscosity, cSt at 40°C	D-445	104.26
Viscosity, cSt at 100°C	D-445	11.8
Flash Point, COC °C (°F)	D-92	215 (419)
Pour Point, °C (°F)	D-97	-17 (2)
ML Reference No.		573360



NOTE:

The information on this Product Data Sheet is believed to be accurate and is typical of current production.

Specifications are subject to change without notice.

Health And Safety Information See separate Safety Data Sheets available on request.

Gard™ and Martin Lubricants™ are trademarks of Martin Lubricants. All other marks are property of their respective owners