

Product No: 574637

Multi-Purpose EP #2 Grease

Lithium-12 Hydroxy Stearate Base; Water Resistant and Excellent Rust Protection

Description

Gard™ Multi-Purpose EP #2 Grease is designed for a wide variety of automotive and industrial applications where a multi-pupose NLGI #2 Extreme Pressure grease is recommended. Gard Multi-Purpose Grease is formulated with a premium extreme pressure, anti-wear, rust, oxidation additive package in a lithium stearate mixed base thickener.



Application

- Recommended for extended service use for industrial applications including roller and ball bearings, electric motor bearings, throw-out bearings, universal joints, chassis, and fifth wheels
- This grease will satisfy 80% of industrial applications

Benefits

- Superior Extreme Pressure (EP) performance
- Lithium/calcium mixed base thickener compatible with most greases
- Water insoluble
- High loading and shock loading capabilities





Product No: 574637

PERFORMANCE RATING

NLGI Rated for automotive chassis usage

TYPICAL PROPERTIES		
	Method	Typical
NLGI Consistency		2
Thickener		Lithium-12 Stearate
Texture		Smooth, Tacky
Color, Observed		Blue
Worked Penetration, 60 Strokes	D-217	265-295
Dropping Point °C (°F)	D-2265	185 (365) Min.
Water Washout @ 100°F	D-1264	5.0
Timken OK Load, lb	D-2509	50
Four-Ball EP Weld Point, kgf	D-2596	300 (250 Min)
Approximate Temperature Range, °C (°F)		-18 to 129 (0 to 265)
Martin Lubricants Bulk Number		501770
MSP Code		NLG-1001

The information on this Product Data Sheet is believed to be accurate and is typical of current production. Specifications are subject to change without notice. For additional qualifications, please contact Martin Technical Service Department.

Health and Safety Information: See separate Safety Data Sheets available on request.

Gard™ and Martin Lubricants™ are trademarks of Martin Lubricants. All other marks are property of their respective owners.

