

## Product Information



### **Hi-Temp Lithium Grease EP2**

**High Temperature Wheel Bearing Grease  
Lithium Complex Base  
Water Resistant and Excellent Rust Protection**

---

#### DESCRIPTION

**Xtreme™ Hi-Temp Grease EP 2** is multi-purpose lithium complex grease fortified with specialty additives to meet severe requirements of wide range of applications of the industry. This grease is capable of operations from a minus 40 degrees Fahrenheit to 350 degrees Fahrenheit.

**Xtreme™ Hi-Temp Grease EP 2** resists thinning in bearings, thereby minimizing leakage to extended long life service. This grease protects steel and copper alloy bearings against rust and corrosion. It provides effective protection for ball joints, drive shafts and other parts subjected to high pressure and shock loading.

---

#### APPLICATION

**Xtreme™ Hi-Temp Grease EP 2** is recommended for extended service in heavy duty automotive, trucks, buses, farm tractors, construction equipment, high temp wheel bearings (disc brakes), roller & ball bearings, electric motor bearings, throw-out bearings, universal joints, chassis, fifth wheel, etc.

---

#### BENEFITS

- Excellent mechanical stability
- Wide temperature operating range
- Good water resistance
- Outstanding extreme pressure protection

---

#### PERFORMANCE

NLGI Rated GC-LB for Automotive Chassis and Bearing Usage

---

#### TYPICAL PROPERTIES

	Method	TYPICAL
Thickener		Lithium Complex
NLGI Grade		2
Texture	Visual	Smooth, Tacky
Color, Observed		Red
Worked Penetration	D-217	285
Dropping Point, °C. (°F)	D-2265	288 (550) Min.
Water Washout @ 79.4°C, % wt	D-1264	3.0
Weld Load, kg	D-2596	315
Timken OK Load, lbs.	D-2509	60



**MARTIN LUBRICANTS, A Division of Martin Operating Partnership L.P.**  
SMACKOVER, AR 71762 ■ USA ■ PHONE 800 864-6275 ■ [www.martinlubricants.com](http://www.martinlubricants.com)

## Product Information

---

Martin Lubricants Item Number  
MSP Code

501878  
NL-1325

---

The information on this Product Data Sheet is believed to be accurate and is typical of current production. Specifications are subject to change without notice.

**Health And Safety Information** See separate Safety Data Sheets available on request.

**Xtreme™** and **Martin Lubricants™** are trademarks of Martin Lubricants. All other marks are property of their respective owners.



**MARTIN LUBRICANTS, A Division of Martin Operating Partnership L.P.**  
SMACKOVER, AR 71762 ■ USA ■ PHONE 800 864-6275 ■ [www.martinlubricants.com](http://www.martinlubricants.com)