



### DESCRIPTION

SynGard™ Calcium Sulfonate EP 2 Grease is high performance extreme pressure grease exhibiting outstanding film strength and resistance to corrosive saltwater environments. With a Timken OK load of 65 lbs., SynGard Calcium Sulfonate EP 2 Grease is recommended for the most severe applications in industry. It is particularly suitable for high speed bearings and centralized lubrication systems. Exhibiting excellent water repellency, oxidation resistance and a wide operating temperature range.

### BENEFITS

- ❑ Excellent performance under heavy loads
- ❑ Protects equipment from rust
- ❑ Does not drip out under running conditions
- ❑ Extraordinary performance at high temperatures
- ❑ Protects equipment from rusting under humid and water ingress conditions

### APPLICATION

SynGard Calcium Sulfonate EP 2 Grease is recommended for use in automotive, as well as extreme pressure applications in the construction, mining, agricultural, logging and hauling industries and anyplace where a shear stable, high load carrying, corrosion resistant grease is required.

TYPICAL PROPERTIES	METHOD	SynGard Calcium Sulfonate EP #2 Grease
Thickener		Calcium Sulfonate
NLGI Grade		2
Texture	Visual	Smooth
Color, Observed		Amber
Worked Penetration	D-217	265-295
Dropping Point, °C (°F)	D-2265	288 (550) Min.
Wheel Bearing Leakage, gm	D-1263	5.0 Max
Water Washout @ 79.4°C, % wt	D-1264	3.0
Base Oil Viscosity @ 40°C, cSt	D-445	220
Weld Load, kg	D-2596	620
Load Wear Index	D-2596	65
Timken OK Load, lb	D-2509	65



**NOTE:**

The information on this Product Data Sheet is believed to be accurate and is typical of current production.

Specifications are subject to change without notice.

**Health And Safety Information** See separate Safety Data Sheets available on request.

**SynGard™ and Martin Lubricants™** are trademarks of Martin Lubricants. All other marks are property of their respective owners