

## Product Information



### ***Tractor Hydraulic Fluid***

***Universal Farm, Construction and Logging Lubricant  
For Transmission, Final Drive and Hydraulic Applications***

---

#### **DESCRIPTION**

**Xtreme™ Tractor Hydraulic Fluid** is a universal hydraulic and transmission fluid for farm tractors, construction equipment and logging equipment where a single fluid services the transmission, power steering and final drives for two wheel and four wheel drive equipment.

**Xtreme™ Tractor Hydraulic Fluid** is formulated using base oils specially selected for their resistance to oxidation, clarity and thermal stability. Drive-train additives are then added to enhance performance and provide extreme pressure (EP) protection for highly loaded gears. **Xtreme™ Tractor Hydraulic Fluid** is a straight SAE 20 weight product and is designed for use in warmer climates, where low temperature operation is not an issue.

---

#### **APPLICATION**

- Farm tractors
- Construction equipment such as dozers, front end loaders, excavators
- Logging equipment such as skidders, feller bunchers, harvesters, loaders

---

#### **BENEFITS**

- Protects gears with EP additives
- Inhibits rust, corrosion, and foaming and aids in water tolerance
- Mixes easily with all OEM fluids

---

#### **PERFORMANCE LEVELS**

John Deere	J20A, B (Hy-Gard), J14B (303 Fluid), J14A/C,
Case/ IH	143, 145, MS-1204, MS-1205, MS 1206 TCH
Ford / New Holland	ESN-M2C, 134B, C
Massey Ferguson	PF821, M-1127, M-1129, Permatran, Q-1722
AGCO, White, Allis-Chalmers	
Caterpillar	TO-2



**MARTIN LUBRICANTS, A Division of Martin Operating Partnership L.P.**  
SMACKOVER, AR 71762 ■ USA ■ PHONE 800 864-6275 ■ [www.martinlubricants.com](http://www.martinlubricants.com)

## Product Information

---

<b>TYPICAL PROPERTIES</b>	<b>Method</b>	<b>THF</b>
API Gravity	D-4052	32.8
Specific Gravity at 15.6°C	D-4052	0.8612
Viscosity, cSt at 100°C	D-445	6.96
Viscosity Index	D-2270	118
Copper Strip Corrosion	D-130	1A
Foam, Sequence II	D-892	0 / 0
Flash Point, COC °C (°F)	D-92	233 (451)
Pour Point, °C (°F)	D-97	-39 (-38)
Color, ASTM	D-1500	3.0
SAE Equivalent	J-300	20
ML Bulk Number		566872

---

The information on this Product Data Sheet is believed to be accurate and is typical of current production. Specifications are subject to change without notice.

**Health And Safety Information** See separate Safety Data Sheets available on request.

**Xtreme™** and **Martin Lubricants™** are trademarks of Martin Lubricants. All other marks are property of their respective owners.

Use **Xtreme® Heavy-Duty Universal Tractor Hydraulic Fluid** for all-season or cold weather use.



**MARTIN LUBRICANTS, A Division of Martin Operating Partnership L.P.**  
SMACKOVER, AR 71762 ■ USA ■ PHONE 800 864-6275 ■ [www.martinlubricants.com](http://www.martinlubricants.com)