



**GL-5 SAE
GEAR OIL**

Multi-Purpose Automotive/HD Gear Oil
Non-Limited Slip; Excellent Corrosion Protection



Fleet/Farm/Off-Road

REV: 06.08.2017



DESCRIPTION

Xtreme™ GL-5 SAE Gear Lubricants are premium quality extreme pressure gear oils for final drives and heavy gear applications. Designed for all hypoid differentials (conventional) and manual transmissions in passenger cars, light trucks, sport utility vehicles, vans, and heavy-duty trucks where an API GL-5 or MT-1 fluid is specified.

BENEFITS

- Excellent thermal and oxidation stability
- Excellent resistance to foaming
- Extreme pressure additives prevent gear scuffing and pitting
- Prevents formation of rust and sludge throughout the system
- Excellent corrosion protection of copper and brass
- Excellent hydrolytic stability

APPLICATION

- Ideal for automotive and truck manual transmissions and differentials.
- Excellent for off-road construction and agricultural equipment.
- For use in heavy duty trucks and buses as a final drive lubricant.

PERFORMANCE

Performance Levels

- API - Service Level GL-5, GL-4
- SAE J-2360
- Military Spec - MIL-L-2105D, 2015E
- Mack Truck - GO-G, GO-H

TYPICAL PROPERTIES	METHOD	SAE 80W-90
Specific Gravity at 60°F	D-4052	0.891
Viscosity, cSt at 40°C	D-445	130.1
Viscosity, cSt at 100°C	D-445	14.0
Viscosity Index	D-2270	105
Flash Point, COC °C (°F)	D-92	219 (426)
Pour Point, °C (°F)	D-97	-36 (33)
ML Reference No.		569256



NOTE:

The information on this Product Data Sheet is believed to be accurate and is typical of current production. Specifications are subject to change without notice. For additional qualifications, please contact Martin Technical Service Department.

Health And Safety Information See separate Safety Data Sheets available on request.

Xtreme™ and Martin Lubricants™ are trademarks of Martin Lubricants. All other marks are property of their respective owners