



PIONEERING PREMIUM **PROTECTION** AND PERFORMANCE



SYNGARD CALCIUM SULFONATE GREASE

Severe operating environments require a premium lubricant that can repel water, resist rust, and perform under heavy loads. SynGard Calcium Sulfonate is an extreme pressure #2 grease crafted using calcium sulfonate thickeners that provide outstanding film strength to protect moving surfaces.

Recommended for high-speed bearings and centralized lubrication systems as well as use in automotive applications. Also ideal for use in extreme pressure applications where a shear-stable, high load carrying, corrosion-resistant grease is required such as construction, mining, agricultural, logging, and hauling.

- **Rated GC-LB for automotive chassis and bearing usage**
- **Resistance to corrosive saltwater environments, humidity, and water ingress conditions**
- **Timken OK load of 65 lbs.**
- **Wide operating temperature range**
- **Does not drip out under running conditions**



TYPICAL PROPERTIES	METHOD	MULTI-PURPOSE GREASE
Thickner Soap Type		Calcium Sulfonate Complex
NLGI	D-217	#2
Color Visual	D-1524	Amber
Appearance Visual		Smooth
Penetration, Worked	D-217	265 - 295
Dropping Point, °F	D-2265	288 (550) Min.
Wheel Bearing Leakage, gm	D-1263	5.0 Max
Water Washout @ 79.4°C, % wt	D-1264	3.0
Weld Load, kg	D-2596	620
Load Wear Index	D-2596	65
Timken OK Load, lb	D-2509	65
KINEMATIC BASE OIL VISCOSITY		
40°C, cSt	D-445	460
100°C, cSt	D-445	30.2
ORDERING INFORMATION		
PART NUMBER	SIZE	PACKAGE STYLE
573423	1/120#	KEG
569467	1/35#	PAIL
590485	1/400#	TOTE
501981	40/14 OZ	4-10 PACK SHRINK CASE
501716	BULK	NONE



WWW.SYNGARDOIL.COM

484 East 6th Street | Smackover, Arkansas | 71762
To become a dealer or distributor, call: 800.864.6275

SCAN FOR MORE
INFO ON SYNGARD'S
GREASE PRODUCTS.

