



XTREME FLUID 334

Construction, Farm, & Logging
Mobile Equipment Fluid



Fleet/Farm/Off-Road

REV: 02.15.2018



DESCRIPTION

Xtreme™ Fluid 334 is designed to be a universal, multi-purpose lubricant for construction, farm, and logging equipment. Manufactured with base oil and additives that provide 3 season performance in spring, summer, and fall in addition to providing 3 layers of protection including anti-wear, rust, and oxidation. Xtreme Fluid 334 will provide an economical solution in the 4 applications found in common sump systems that contain wet brakes, hydraulics, final drives, and transmissions. This product is ideally suited for equipment that may be aging and requires frequent fluid replacement. Not recommended for equipment manufactured after 1974.

BENEFITS

- ▣ Protects system components with anti-wear additives
- ▣ Inhibits rust and corrosion
- ▣ Economical fluid for aging equipment or frequent fluid replacement
- ▣ Three-season protection

APPLICATION

- Construction equipment
- Farm tractors
- Logging equipment such as skidders, feller bunchers, harvesters, loaders

TYPICAL PROPERTIES	METHOD	SAE 20
API Gravity	D-4052	22.5
Specific Gravity at 15.6°C	D-4052	0.919
Viscosity, cSt at 100°C	D-445	6.8
Viscosity, cSt at 40°C	D-445	60.0
Flash Point, COC °C (°F)	D-92	177 (350)
Pour Point, °C (°F)	D-97	-32 (-26)
SAE Equivalent	J-300	20
ML Reference No.		503790



NOTE:

The information on this Product Data Sheet is believed to be accurate and is typical of current production. Specifications are subject to change without notice. For additional qualifications, please contact Martin Technical Service Department.

Health And Safety Information See separate Safety Data Sheets available on request.

Xtreme™ and Martin Lubricants™ are trademarks of Martin Lubricants. All other marks are property of their respective owners