



DESCRIPTION

Xtreme™ Global Multi-Vehicle ATF is an ultra-premium, synthetic blend automatic transmission fluid designed to service most foreign and domestic vehicles sold in the United States since 1983. This product eliminates the need to stock multiple brands and types of transmission fluids to service specific, limited applications.

Xtreme Global Multi-Vehicle ATF has outstanding low temperature properties, controlled frictional characteristics, outstanding resistance to oxidation and can be used in many industrial applications calling for premium hydraulic oils where long life and superior performance are required.

BENEFITS

- ❑ Eliminates the need to stock numerous special ATFs
- ❑ Synthetic components give outstanding oxidation resistance and extended service life
- ❑ Mixes safely with most OEM fluids
- ❑ Proper frictional control for special transmission requirements

APPLICATION

Martin Lubricants has performance data to support in applications calling for the following specifications:

- General Motors vehicles requiring DEXRON®-II, DEXRON®-IIE, DEXRON®-III G & H
- Ford Motors vehicles requiring MERCON® & MERCON® V
- Chrysler vehicles requiring 7176, ATF+, ATF+2, ATF+3, or ATF+4
- Honda/Acura ATF Z1
- Toyota/Lexus Type T, T-III, T-IV, WS
- JASO 1A ATF
- Nissan/Infiniti Matic-D, Matic-J, Matic-K, Matic-S
- Mitsubishi Diamond SP-II, Diamond SP-III
- Hyundai SP-II, SP-III
- BMW LAA2634, LT71141
- Jaguar - All
- Mercedes - ZF TE-ML: 09, 11A/B
- Volvo (except 5-speed)
- Allison heavy-duty transmission requiring C-4 or C-3 fluids

IMPORTANT NOTE: Not recommended for use in CVT transmissions nor where dual pump fluid is required. For additional qualifications, please contact Martin Lubricants Technical Service Department.

TYPICAL PROPERTIES	METHOD	Global MV ATF
Color	Report	Red
API Gravity	D-4052	33.9
Specific Gravity at 15.6°C	D-1298	0.8554
Viscosity, cSt at 40°C	D-445	34.1
Viscosity, cSt at 100°C	D-445	7.7
Viscosity Index	D-2270	207
Flash Point, °C (°F)	D-92	190 (374)
Pour Point, °C (°F)	D-97	-51 (-60)
ML Reference No.		571073



NOTE:

The information on this Product Data Sheet is believed to be accurate and is typical of current production. Specifications are subject to change without notice. For additional qualifications, please contact Martin Technical Service Department.

Health And Safety Information See separate Safety Data Sheets available on request.

Xtreme™ and Martin Lubricants™ are trademarks of Martin Lubricants. All other marks are property of their respective owners